

Safety Data Sheet dated 7/10/2022, version 7.0 This version cancels and substitutes any previous version

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Mixture identification:

Trade name: NO ODOR

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use:

Anti Odour Treatment

1.3. Details of the supplier of the safety data sheet

Company:

ERRECOM SPA

Via Industriale, 14

Corzano (BS) Italy

Tel. +39 030/9719096

Competent person responsible for the safety data sheet:

lab@errecom.it

1.4. Emergency telephone number

+39 02-6610-1029 Poison Control Center Niguarda Ca' Granda - Milano - ITALY

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

EC regulation criteria 1272/2008 (CLP)

Aquatic Chronic 3, Harmful to aquatic life with long lasting effects.

Adverse physicochemical, human health and environmental effects:

No other hazards

2.2. Label elements

Hazard pictograms:

None

Hazard statements:

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements:

P501 Dispose of contents/container in accordance with applicable regulations.

Special Provisions:

None

Special provisions according to Annex XVII of REACH and subsequent amendments:

None

2.3. Other hazards

No PBT, vPvB or endocrine disruptor substances present in concentration >= 0.1%

Other Hazards:

No other hazards

SECTION 3: Composition/information on ingredients

3.1. Substances

N.A.

3.2. Mixtures

Hazardous components within the meaning of the CLP regulation and related classification:

NO ODOR/7.0



Qty	Name	Ident. Numb	er	Classification
>= 7% - < 10%	propan-2-ol	Index number: CAS: EC:	603-117-00-0 67-63-0 200-661-7	 2.6/2 Flam. Liq. 2 H225 3.3/2 Eye Irrit. 2 H319 3.8/3 STOT SE 3 H336
10/			01-21194575 58-25-XXXX	
>= 1% - < 2.5%	ethanol	Index number: CAS: EC: REACH No.:	603-002-00-5 64-17-5 200-578-6 01-21194576 10-43-XXXX	2.6/2 Flam. Liq. 2 H225 3.3/2 Eye Irrit. 2 H319
>= 0.25% - < 0.5%	n-ethyl-n-soya morpholinium ethosulphate	CAS: EC: REACH No.:	61791-34-2 263-167-0 01-21207636 56-43-XXXX	 3.1/4/Oral Acute Tox. 4 H302 3.2/1A Skin Corr. 1A H314 3.3/1 Eye Dam. 1 H318 4.1/A1 Aquatic Acute 1 H400 M=10. 4.1/C1 Aquatic Chronic 1 H410 M=1. Specific Concentration Limits: C >= 50%: Skin Corr. 1A H314 10% <= C < 50%: Skin Irrit. 2 H315 C >= 5%: Eye Dam. 1 H318 1% <= C < 5%: Eye Irrit. 2 H319

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

Wash with plenty of water and soap.

In case of eyes contact:

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. In case of Ingestion:

Do not under any circumstances induce vomiting. OBTAIN A MEDICAL EXAMINATION IMMEDIATELY.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

4.2. Most important symptoms and effects, both acute and delayed None

4.3. Indication of any immediate medical attention and special treatment needed Treatment:

None

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Water.

Carbon dioxide (CO2).

Extinguishing media which must not be used for safety reasons:

NO ODOR/7.0



None in particular.

5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

5.3. Advice for firefighters

Use suitable breathing apparatus.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non emergency personnel:

Wear personal protection equipment.

Remove persons to safety.

See protective measures under point 7 and 8.

For emergency responders:

Wear personal protection equipment.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities

Suitable material for taking up: absorbing material, organic, sand

6.3. Methods and material for containment and cleaning up

Wash with plenty of water.

6.4. Reference to other sections

See also section 8 and 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Advice on general occupational hygiene:

Contamined clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

7.2. Conditions for safe storage, including any incompatibilities

Keep container tightly closed. To maintain product quality, do not store in heat or direct sunlight. Keep in a dry, cool and well-ventilated place.

Do not store at temperatures below + 5 ° C / + 41 ° F.

Keep away from food, drink and feed.

Incompatible materials:

See subsection 10.5

Instructions as regards storage premises:

Cool and adequately ventilated.

7.3. Specific end use(s)

Information not available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

propan-2-ol - CAS: 67-63-0



```
ACGIH - TWA: 200 ppm - STEL: 400 ppm
            MAK - TWA(8h): 500 mg/m3, 200 ppm - STEL(15min): 1000 mg/m3, 400 ppm
             VLA - TWA(8h): 500 mg/m3, 200 ppm - STEL(15min): 1000 mg/m3, 400 ppm
             VLEP - STEL(15min): 980 mg/m3, 400 ppm
            WEL - TWA(8h): 999 mg/m3, 400 ppm - STEL(15min): 1250 mg/m3, 500 ppm
             TLV - TWA(8h): 980 mg/m3, 400 ppm - STEL(15min): 1225 mg/m3, 500 ppm
            NDS - TWA(8h): 900 mg/m3 - STEL(15min): 1200 mg/m3
            NPHV - TWA(8h): 500 mg/m3, 200 ppm - STEL(15min): 1000 mg/m3
            MV - TWA(8h): 500 mg/m3, 200 ppm - STEL(15min): 2000 mg/m3, 800 ppm
             GVI - TWA(8h): 999 mg/m3, 400 ppm - STEL(15min): 1250 mg/m3, 500 ppm
             TLV (CZ) - TWA(8h): 500 mg/m3, 200 ppm - STEL(15min): 1000 mg/m3, 400 ppm
             TLV (EST) - TWA(8h): 350 mg/m3, 150 ppm - STEL(15min): 600 mg/m3, 250 ppm
      ethanol - CAS: 64-17-5
            ACGIH - STEL: 1000 ppm - Notes: A3 - URT irr
             AGW - TWA(8h): 380 mg/m3, 200 ppm - STEL(15min): 1520 mg/m3, 800 ppm
            MAK - TWA(8h): 380 mg/m3, 200 ppm - STEL(15min): 1520 mg/m3, 800 ppm
             VLA - STEL(15min): 1910 mg/m3, 1000 ppm
             VLEP - TWA(8h): 1900 mg/m3, 1000 ppm - STEL(15min): 9500 mg/m3, 5000 ppm
            WEL - TWA(8h): 1920 mg/m3, 1000 ppm
             TLV (GR) - TWA(8h): 1900 mg/m3, 1000 ppm
             GVI - TWA(8h): 1900 mg/m3, 1000 ppm
            NDS - TWA(8h): 1900 mg/m3
            NPHV - TWA(8h): 960 mg/m3, 500 ppm - STEL(15min): 1920 mg/m3
             TLV - TWA(8h): 1000 ma/m3
             TLV (CZ) - TWA(8h): 1000 mg/m3, 522 ppm - STEL(15min): 3000 mg/m3, 1566 ppm
             TLV (EST) - TWA(8h): 1000 mg/m3, 500 ppm - STEL(15min): 1900 mg/m3, 1000 ppm
DNEL Exposure Limit Values
      propan-2-ol - CAS: 67-63-0
            Consumer: 26 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic
            effects
            Worker Industry: 500 mg/m<sup>3</sup> - Consumer: 89 mg/m<sup>3</sup> - Exposure: Human Inhalation -
            Frequency: Long Term, systemic effects
            Worker Industry: 888 mg/kg - Consumer: 319 mg/kg - Exposure: Human Dermal -
            Frequency: Long Term, systemic effects
      ethanol - CAS: 64-17-5
            Worker Industry: 1900 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Short Term,
            local effects
            Worker Industry: 950 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Long Term,
            systemic effects
            Worker Industry: 343 mg/kg - Exposure: Human Dermal - Frequency: Long Term,
            systemic effects
PNEC Exposure Limit Values
      propan-2-ol - CAS: 67-63-0
            Target: Fresh Water - Value: 140.9 mg/L
            Target: Marine water - Value: 140.9 mg/L
            Target: Freshwater sediments - Value: 552 mg/kg
            Target: Aquatic, periodic release - Value: 140.9 mg/L
            Target: Microorganisms in sewage treatments - Value: 2251 mg/L
            Target: Marine water sediments - Value: 552 mg/kg
            Target: Soil (agricultural) - Value: 28 mg/kg
      ethanol - CAS: 64-17-5
           Target: Fresh Water - Value: 0.96 mg/L
            Target: Marine water - Value: 0.79 mg/L
            Target: Freshwater sediments - Value: 36 mg/kg
            Target: Marine water sediments - Value: 2.9 mg/kg
```



Target: Aquatic, periodic release - Value: 2.75 mg/L

Target: Microorganisms in sewage treatments - Value: 580 mg/L

Target: Secondary poisoning - Value: 0.72 mg/kg Target: Soil (agricultural) - Value: 0.63 mg/kg

8.2. Exposure controls

Eye protection:

Not needed for normal use. Anyway, operate according good working practices.

Protection for skin:

No special precaution must be adopted for normal use.

Protection for hands:

Not needed for normal use.

Respiratory protection:

Not needed for normal use.

Thermal Hazards:

None

Environmental exposure controls:

None

Appropriate engineering controls:

None

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Method:	Notes:
Physical state:	Liquid		
Colour:	Colourless		
Odour:	characteristic		
Melting point/freezing point:	N.A.		
Boiling point or initial boiling point and boiling range:	N.A.		
Flammability:	N.A.		
Lower and upper explosion limit:	N.A.		
Flash point:	77 ° C	ASTM-D 93	
Auto-ignition temperature:	N.A.		
Decomposition temperature:	N.A.		
pH:	7,1		
Kinematic viscosity:	N.A.		
Solubility in water:	total		
Solubility in oil:	N.A.		
Partition coefficient n-octanol/water (log value):	N.A.		
Vapour pressure:	N.A.		
Density and/or relative density:	0.985 g/mL (+20°C/+68°F)	ASTM-D4052	
Relative vapour density:	N.A.		

Particle characteristics:

Particle size: N.A. -- --

9.2. Other information



No other relevant information

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions

10.2. Chemical stability

Stable under normal conditions

10.3. Possibility of hazardous reactions

None

10.4. Conditions to avoid

Store away from heat.

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

No data available

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008 Toxicological information of the product:

a) acute toxicity

Not classified

Based on available data, the classification criteria are not met

b) skin corrosion/irritation

Not classified

Based on available data, the classification criteria are not met

c) serious eye damage/irritation

Not classified

Based on available data, the classification criteria are not met

d) respiratory or skin sensitisation

Not classified

Based on available data, the classification criteria are not met

e) germ cell mutagenicity

Not classified

Based on available data, the classification criteria are not met

f) carcinogenicity

Not classified

Based on available data, the classification criteria are not met

g) reproductive toxicity

Not classified

Based on available data, the classification criteria are not met

h) STOT-single exposure

Not classified

Based on available data, the classification criteria are not met

i) STOT-repeated exposure

Not classified

Based on available data, the classification criteria are not met

i) aspiration hazard

Not classified

Based on available data, the classification criteria are not met

Toxicological information of the main substances found in the product:

propan-2-ol - CAS: 67-63-0

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat 4710 mg/kg



Test: LD50 - Route: Skin - Species: Rat 12800 mg/kg

Test: LC50 - Route: Inhalation - Species: Rat 72.6 mg/L - Duration: 4h

Test: LD50 - Route: Skin - Species: Rabbit 6290 mg/kg

ethanol - CAS: 64-17-5

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 2000 mg/kg Test: LD50 - Route: Skin - Species: Rabbit > 2000 mg/kg

Test: LC50 - Route: Inhalation - Species: Mouse > 20 mg/L - Duration: 4h

n-ethyl-n-soya morpholinium ethosulphate - CAS: 61791-34-2

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat 1.670 mg/kg

b) skin corrosion/irritation:

Test: Skin Corrosive - Route: Skin - Species: Rabbit Positive

c) serious eve damage/irritation:

Test: Eye Corrosive - Route: Eyes - Species: bovine cornea Positive - Source: OECD TG 437 - Notes: Substance concentracion: 35%

e) germ cell mutagenicity:

Test: Ames test - Species: Salmonella Typhimurium Negative - Source: OECD TG 471

- Notes: Metabolic activation: with and without

11.2. Information on other hazards

Endocrine disrupting properties:

No endocrine disruptor substances present in concentration >= 0.1%

SECTION 12: Ecological information

12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.

The product is classified: Aquatic Chronic 3 - H412

propan-2-ol

a) Aquatic acute toxicity:

Endpoint: EC0 - Species: Fish 10000 mg/L - Duration h: 48 - Notes: Pimephales promelas

Endpoint: LC50 - Species: Fish > 1400 mg/L - Duration h: 96 - Notes: Lepomis

macrochirus

Endpoint: LC50 - Species: Fish 6550 mg/L - Duration h: 96 - Notes: Pimephales

promelas

ethanol

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish > 11200 mg/L - Duration h: 96

Endpoint: EC50 - Species: Daphnia > 12300 mg/L - Duration h: 48 - Notes: Species:

Daphnia magna

Endpoint: EC50 - Species: Algae > 275 mg/L - Duration h: 72 - Notes: Species:

Chlorella vulgaris

n-ethyl-n-soya morpholinium ethosulphate

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Daphnia 0.09 mg/L - Duration h: 48 - Notes: OECD TG 202

- Species: Daphnia magna - Test type: static test

e) Plant toxicity:

Endpoint: EC50 - Species: Algae 0.021 mg/L - Duration h: 72 - Notes: OECD TG 201 -

Species: Pseudkirchneriella subcapitata - Test type: growth inhibitor

Endpoint: NOEC - Species: Algae 0.016 mg/L - Duration h: 72 - Notes: OECD TG 201 -

Species: Pseudkirchneriella subcapitata - Test type: growth inhibitor

12.2. Persistence and degradability

propan-2-ol - CAS: 67-63-0



Biodegradability: Readily biodegradable

ethanol - CAS: 64-17-5

Biodegradability: Readily biodegradable - Test: Solubility in water - Notes: 1000 -

10000 mg/L

12.3. Bioaccumulative potential

propan-2-ol - CAS: 67-63-0

Bioaccumulation: Not bioaccumulative - Test: Kow - Partition coefficient 0.05

ethanol - CAS: 64-17-5

Bioaccumulation: Not bioaccumulative - Test: Kow - Partition coefficient 0.350000-

12.4. Mobility in soil

N.A.

12.5. Results of PBT and vPvB assessment

vPvB Substances: None - PBT Substances: None

12.6. Endocrine disrupting properties

No endocrine disruptor substances present in concentration >= 0.1%

12.7. Other adverse effects

None

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Recover if possible. In so doing, comply with the local and national regulations currently in force.

SECTION 14: Transport information

14.1. UN number or ID number

Not classified as dangerous in the meaning of transport regulations.

14.2. UN proper shipping name

N.A.

14.3. Transport hazard class(es)

N.A.

14.4. Packing group

N.A.

14.5. Environmental hazards

ADR-Enviromental Pollutant: No IMDG-Marine pollutant: No

14.6. Special precautions for user

N.A.

14.7. Maritime transport in bulk according to IMO instruments

N.A.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Dir. 98/24/EC (Risks related to chemical agents at work)

Dir. 2000/39/EC (Occupational exposure limit values)

Regulation (EC) n. 1907/2006 (REACH)

Regulation (EC) n. 1272/2008 (CLP)

Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013

Regulation (EU) n. 2020/878

Regulation (EU) n. 286/2011 (ATP 2 CLP)

Regulation (EU) n. 618/2012 (ATP 3 CLP)

Regulation (EU) n. 487/2013 (ATP 4 CLP)



Regulation (EU) n. 605/2014 (ATP 6 CLP)
Regulation (EU) n. 2015/1221 (ATP 7 CLP)
Regulation (EU) n. 2016/918 (ATP 8 CLP)
Regulation (EU) n. 2016/1179 (ATP 9 CLP)
Regulation (EU) n. 2017/776 (ATP 10 CLP)

Regulation (EU) n. 944/2013 (ATP 5 CLP)

Regulation (EU) n. 2018/669 (ATP 11 CLP)

Regulation (EU) n. 2018/1480 (ATP 13 CLP)

Regulation (EU) n. 2019/521 (ATP 12 CLP) Regulation (EU) n. 2020/217 (ATP 14 CLP)

Regulation (EU) n. 2020/1182 (ATP 15 CLP)

Regulation (EU) n. 2021/643 (ATP 16 CLP)

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

Restrictions related to the product:

Restriction 3

Restriction 40

Restrictions related to the substances contained:

Restriction 75

Where applicable, refer to the following regulatory provisions:

Directive 2012/18/EU (Seveso III)

Regulation (EC) nr 648/2004 (detergents).

Dir. 2004/42/EC (VOC directive)

Provisions related to directive EU 2012/18 (Seveso III):

Seveso III category according to Annex 1, part 1

None

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for the mixture.

SECTION 16: Other information

Full text of phrases referred to in Section 3:

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H318 Causes serious eye damage.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H315 Causes skin irritation.

Hazard class and	Code	Description	
hazard category			
Flam. Liq. 2	2.6/2	Flammable liquid, Category 2	
Acute Tox. 4	3.1/4/Oral	Acute toxicity (oral), Category 4	
Skin Corr. 1A	3.2/1A	Skin corrosion, Category 1A	
Skin Irrit. 2	3.2/2	Skin irritation, Category 2	
Eye Dam. 1	3.3/1	Serious eye damage, Category 1	
Eye Irrit. 2	3.3/2	Eye irritation, Category 2	
STOT SE 3	3.8/3	Specific target organ toxicity - single exposure,	
		Category 3	



Aquatic Acute 1	4.1/A1	Acute aquatic hazard, category 1
Aquatic Chronic 1	4.1/C1	Chronic (long term) aquatic hazard, category 1
Aquatic Chronic 3	4.1/C3	Chronic (long term) aquatic hazard, category 3

This safety data sheet has been completely updated in compliance to Regulation 2020/878. Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Classification according to Regulation (EC) Nr. 1272/2008	Classification procedure
Aquatic Chronic 3, H412	Calculation method

This document was prepared by a competent person who has received appropriate training. Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

ADR: European Agreement concerning the International Carriage of

Dangerous Goods by Road.

ATE: Acute Toxicity Estimate

ATEmix: Acute toxicity Estimate (Mixtures)

CAS: Chemical Abstracts Service (division of the American Chemical

Society).

CLP: Classification, Labeling, Packaging.

DNEL: Derived No Effect Level.

EINECS: European Inventory of Existing Commercial Chemical Substances.

GefStoffVO: Ordinance on Hazardous Substances, Germany.

GHS: Globally Harmonized System of Classification and Labeling of

Chemicals.

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport

Association" (IATA).

ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization"

(ICAO).

IMDG: International Maritime Code for Dangerous Goods. INCI: International Nomenclature of Cosmetic Ingredients.

KSt: Explosion coefficient.

LC50: Lethal concentration, for 50 percent of test population.

LD50: Lethal dose, for 50 percent of test population.

PNEC: Predicted No Effect Concentration.

RID: Regulation Concerning the International Transport of Dangerous Goods

bv Rail.

STEL: Short Term Exposure limit.
STOT: Specific Target Organ Toxicity.
TLV: Threshold Limiting Value.
TWA: Time-weighted average



WGK: German Water Hazard Class.