

YT-1200H-S-R290

Explosimètre pour gaz combustible

**! Calibré
spécifiquement
au R290**



FONCTIONNALITÉS

- Surveille en permanence la concentration de R290 dans l'atmosphère dans la zone de travail et alerte immédiatement l'opérateur lorsque la concentration dépasse les seuils d'alerte et se rapproche du seuil d'explosivité.
- Indispensable à tous les techniciens manipulant des fluides A3 dont le R290 afin de garantir leur sécurité.

CARACTÉRISTIQUES

- Affiche la concentration en %LEL (limite d'explosivité inférieure)
- Batterie Li-ion 3.7V
- Deux seuils d'alarmes paramétrables à 20% et 50% LEL par défaut
- Coque de protection
- Crochet pour fixer à la ceinture
- Température de fonctionnement -20 à +80°C
- Signaux d'alarmes visuels et sonores
- ATEX II 2G Ex ia IIC T4 Ga IP66



YT-1200H-S-R290

Combustible Gas Explosimeter

 ***Specially
calibrated for
R290***



FEATURES

- Monitors the concentration of R290 in the atmosphere continuously within the work area and immediately alerts the operator when the concentration exceeds warning thresholds and approaches the explosivity threshold.
- Essential for all technicians handling A3 refrigerants, including R290, to ensure their safety

SPECIFICATIONS

- Display concentration in %LEL (Lower explosive limit)
- Li-ion battery 3.7V
- Two adjustable alarm thresholds set at 20% and 50% LEL by default
- Protective housing
- Belt clip for attachment
- Operating temperature -20 to +80°C
- Visual and audible alarm signals
- **ATEX II 2G Ex ia IIC T4 Ga IP66**

